

Supervised Learning Algorithms

Accuracy

Related terms: Precision, recall, classification metrics, confusion matrix. Explanation: Accuracy measures the proportion of correctly predicted instances out of the total number of instances. It is calculated as $(\text{true positives} + \text{true negatives}) / (\text{total predictions})$. In welding defect classification, high accuracy indicates the model reliably distinguishes between acceptable welds and defects such as porosity or cracks. Example: A model that predicts weld quality on 1,000 samples with 950 correct predictions yields an accuracy of 95%. Practical application: Used for quick assessment of model performance during early prototyping of weld quality prediction systems. Challenges: Accuracy can be misleading when class distribution is imbalanced; a dataset with 95% sound welds could achieve 95% accuracy by always predicting "no defect," masking poor detection of rare defects.

AdaBoost (Adaptive Boosting)

Related terms: Ensemble learning, weak learners, boosting, gradient boosting. Explanation: AdaBoost combines multiple weak classifiers, typically decision stumps, into a strong classifier by iteratively focusing on mis-classified samples. Each iteration assigns higher weights to previously mis-classified instances, encouraging subsequent learners to correct errors. Example: In a weld-parameter prediction task, AdaBoost may use shallow decision trees on features such as current, voltage, and travel speed to improve defect detection. Practical application: Effective for datasets with moderate size where computational resources are limited, such as on-site welding robots with embedded processors. Challenges: Sensitive to noisy labels; outliers in sensor data can cause the algorithm to over-emphasize erroneous samples, degrading performance.

Artificial Neural Network (ANN)

Related terms: Multilayer perceptron, deep learning, activation function, backpropagation. Explanation: An ANN consists of interconnected layers of nodes (neurons) that transform input features through weighted sums and nonlinear activation functions. Supervised training adjusts weights to minimize a loss function using gradient-based optimization. Example: A feed-forward ANN with three hidden layers predicts weld bead geometry from real-time current and voltage waveforms. Practical application: Captures complex, nonlinear relationships between welding parameters and resulting microstructure, enabling adaptive control of welding robots. Challenges: Requires large labeled datasets; overfitting is common when the network is deep relative to the amount of data, necessitating regularization techniques such as dropout or early stopping.

Bias-Variance Tradeoff

Related terms: Overfitting, underfitting, model complexity, generalization error. Explanation: The bias-variance tradeoff describes how prediction error can be decomposed into bias (error from erroneous assumptions) and variance (error from sensitivity to training data). Low-bias, high-variance models (e.g., Deep neural networks) fit training data closely but may not generalize, whereas high-bias, low-variance

models (e.G., Linear regression) may underfit. Example: In weld-defect classification, a simple logistic regression may have high bias, missing subtle defect patterns, while a deep CNN may have low bias but high variance, giving inconsistent results across different welding runs. Practical application: Guides selection of model complexity and regularization strength to achieve robust weld quality prediction. Challenges: Quantifying bias and variance requires techniques such as repeated cross-validation, which can be computationally intensive for large welding datasets.

Bayesian Linear Regression

Related terms: Prior distribution, posterior inference, Gaussian likelihood, regularization. Explanation: Bayesian linear regression treats regression coefficients as random variables with prior distributions. Observing data updates these priors to posteriors via Bayes' theorem, providing a full predictive distribution rather than point estimates. Example: Predicting heat input (J/mm) from welding current and speed, the Bayesian approach yields a mean prediction and credible interval reflecting uncertainty. Practical application: Useful for risk-aware decision making in welding process planning, where confidence bounds inform safety margins. Challenges: Requires specification of appropriate priors; computational cost rises with large feature sets, demanding approximation methods such as variational inference.

Cross-Validation

Related terms: K-fold, stratified sampling, model selection, validation set. Explanation: Cross-validation partitions the dataset into multiple folds, training the model on a subset while validating on the remaining fold. Repeating this process yields an average performance estimate, reducing variance caused by a single train-test split. Example: A 5-fold cross-validation on a dataset of 2,000 weld samples evaluates the stability of a random forest classifier for defect detection. Practical application: Provides reliable performance metrics for hyperparameter tuning in welding-process models where data acquisition is costly. Challenges: In time-series welding data (e.G., Continuous arc monitoring), temporal dependencies must be respected, requiring forward-chaining validation rather than random folds.

Decision Tree

Related terms: CART, impurity measure, leaf node, pruning. Explanation: A decision tree recursively splits the feature space based on criteria such as Gini impurity or information gain, producing a tree structure where each leaf predicts a class label (classification) or a numeric value (regression). Example: A tree that splits first on welding current, then on travel speed, and finally on shielding gas flow to predict the likelihood of porosity. Practical application: Offers interpretability for welding engineers, who can trace how specific parameter thresholds influence defect risk. Challenges: Prone to overfitting; small changes in data can produce vastly different trees, necessitating pruning or ensemble methods.

Elastic Net

Related terms: Lasso, Ridge, regularization path, hyperparameter α . Explanation: Elastic Net combines L1 (Lasso) and L2 (Ridge) penalties to enforce both sparsity and coefficient shrinkage. The loss function adds $\lambda_1 \|\beta\|_1 + \lambda_2 \|\beta\|_2^2$ to the ordinary least-squares term, balancing between feature selection and stability. Example: Modeling weld bead width from a high-dimensional set of sensor readings, Elastic Net discards irrelevant frequencies while keeping correlated features. Practical application: Handles multicollinearity common in multi-sensor welding data, improving model robustness. Challenges: Requires tuning two

regularization parameters, often via nested cross-validation, increasing computational load.

Feature Engineering

Related terms: Feature extraction, dimensionality reduction, domain knowledge, scaling. Explanation: Feature engineering transforms raw sensor data into informative variables that enhance model learning. Techniques include aggregating time-series signals, computing statistical moments, and applying domain-specific formulas (e.G., Heat input = $V \times I \times t$). Example: Converting raw voltage waveforms into peak-to-peak amplitude, RMS value, and spectral power in the 1–5 kHz band for defect classification. Practical application: Improves predictive accuracy of supervised models in welding by emphasizing physically relevant characteristics. Challenges: Manual feature creation is labor-intensive; automated methods (e.G., Auto-encoders) may still require expert validation to avoid spurious correlations.

Gaussian Process Regression (GPR)

Related terms: Kernel function, covariance matrix, Bayesian inference, predictive variance. Explanation: GPR treats regression as a distribution over functions, defined by a mean function and a kernel that encodes similarity between data points. Predictions are Gaussian distributions with mean and variance, offering uncertainty quantification. Example: Predicting weld bead penetration depth from current and voltage using a squared-exponential kernel to capture smooth variations. Practical application: Enables adaptive welding control where the robot adjusts parameters based on confidence-weighted predictions. Challenges: Computationally $O(n^3)$ in the number of training points; scaling to thousands of weld samples requires sparse approximations.

Gradient Boosting

Related terms: Boosting, learning rate, loss function, weak learner. Explanation: Gradient boosting builds an additive model by sequentially fitting weak learners (often shallow trees) to the negative gradient of a loss function. Each new learner corrects residual errors of the ensemble. Example: A gradient-boosted model predicts the probability of cracking based on arc voltage, current, and filler-wire composition. Practical application: Provides high predictive power for complex welding datasets, often outperforming single trees. Challenges: Sensitive to hyperparameters such as learning rate and number of estimators; improper settings can cause overfitting, especially with limited welding data.

Hyperparameter Tuning

Related terms: Grid search, random search, Bayesian optimization, validation set. Explanation: Hyperparameters are configuration settings external to model training (e.G., Tree depth, regularization strength). Tuning searches the hyperparameter space to find values that minimize validation error. Example: Using random search to explore $\text{max_depth} \in \{3, 5, 7, 9\}$ and $\text{learning_rate} \in \{0.01, 0.05, 0.1\}$ For an XGBoost classifier on weld defect data. Practical application: Optimizes model performance without manual trial-and-error, essential for time-critical deployment of welding quality monitors. Challenges: Large search spaces increase computational cost; cross-validation for each configuration can be prohibitive, motivating efficient methods like Bayesian optimization.

K-Nearest Neighbors (k-NN)

Related terms: Distance metric, instance-based learning, lazy learning, Euclidean distance. Explanation: K-NN classifies a query point by majority vote among its k closest training instances, measured by a chosen

distance metric. Regression predicts the average target of those neighbors. Example: Classifying a welding arc segment as “stable” or “unstable” based on the 5 nearest historic arc waveforms. Practical application: Simple baseline for real-time defect detection where model training is minimal. Challenges: Computationally expensive at prediction time for large datasets; performance degrades in high-dimensional spaces due to the curse of dimensionality, common with multi-sensor welding data.

Lasso Regression (Least Absolute Shrinkage and Selection Operator)

Related terms: L1 regularization, sparsity, feature selection, coefficient shrinkage. Explanation: Lasso adds an L1 penalty $\lambda \|\beta\|_1$ to the ordinary least-squares loss, driving many coefficients to exactly zero, thus performing variable selection. Example: Selecting the most influential welding parameters (current, voltage, gas flow) for predicting bead height while discarding redundant sensor channels. Practical application: Reduces model complexity and measurement cost in welding process monitoring. Challenges: When predictors are highly correlated, Lasso arbitrarily selects one, potentially discarding useful information; Elastic Net can mitigate this issue.

Logistic Regression

Related terms: Binary classification, sigmoid function, odds ratio, maximum likelihood. Explanation: Logistic regression models the probability of a binary outcome using the logistic (sigmoid) function applied to a linear combination of input features. Parameters are estimated via maximum likelihood. Example: Predicting the probability that a weld will exhibit lack of fusion based on current, voltage, and travel speed. Practical application: Provides interpretable coefficients (odds ratios) that welding engineers can translate into process guidelines. Challenges: Assumes linear relationship in log-odds; may underperform when defect patterns are highly nonlinear, requiring polynomial features or alternative algorithms.

Loss Function

Related terms: Cost function, objective, mean squared error, cross-entropy. Explanation: The loss function quantifies the discrepancy between predicted outputs and true targets. During supervised training, optimization algorithms minimize this function to improve model parameters. Example: Using mean squared error for regression of weld bead width; using binary cross-entropy for classification of defect presence. Practical application: Choice of loss directly influences model behavior; for imbalanced welding defect data, weighted cross-entropy can emphasize minority classes. Challenges: Non-convex loss surfaces (e.g., Deep neural networks) may trap optimizers in local minima; careful initialization and optimizer selection are required.

Matrix Factorization (e.g., NMF)

Related terms: Dimensionality reduction, latent factors, non-negative matrix factorization, feature compression. Explanation: Matrix factorization decomposes a data matrix into lower-dimensional components, capturing underlying structure. In supervised contexts, factorized features are fed into downstream classifiers. Example: Decomposing a high-dimensional spectrogram of arc voltage into latent bases, then using the coefficients to predict spatter occurrence. Practical application: Reduces computational load for real-time welding monitoring devices. Challenges: Selecting the appropriate rank; over-compression may lose critical defect information.

Model Evaluation Metrics

Related terms: Confusion matrix, ROC curve, precision-recall, F1-score. Explanation: Metrics assess how well a supervised model performs on unseen data. For classification, common metrics include accuracy, precision (positive predictive value), recall (sensitivity), and F1-score (harmonic mean of precision and recall). For regression, metrics include mean absolute error (MAE) and coefficient of determination (R^2). Example: A weld defect classifier achieving precision = 0.92 And recall = 0.78 Indicates few false positives but some missed defects. Practical application: Selecting the appropriate metric aligns model optimization with welding quality objectives (e.G., Prioritizing recall to avoid missing dangerous cracks). Challenges: Metric selection can bias model development; imbalance requires focusing on recall or area under the precision-recall curve rather than accuracy.

Naïve Bayes

Related terms: Bayes theorem, conditional independence, Gaussian NB, multinomial NB. Explanation: Naïve Bayes classifiers apply Bayes theorem assuming feature independence given the class label. Despite the strong assumption, they often perform well in practice. Example: Classifying weld seam images into "defect" or "no defect" using pixel intensity histograms as features. Practical application: Fast training and inference on embedded welding inspection hardware. Challenges: Independence assumption is violated in correlated sensor data, potentially reducing accuracy; smoothing techniques can alleviate zero-probability issues.

Neural Network Regularization (Dropout, L2)

Related terms: Overfitting mitigation, weight decay, stochastic regularization. Explanation: Regularization techniques add constraints to the learning process to prevent overfitting. Dropout randomly deactivates a fraction of neurons during training, while L2 weight decay penalizes large weights. Example: Applying 20% dropout to hidden layers of a weld-parameter predictor to improve generalization on unseen joint configurations. Practical application: Enables deployment of deep models on limited-data welding projects without sacrificing performance. Challenges: Excessive dropout can hinder learning; balancing regularization strength requires careful validation.

Polynomial Regression

Related terms: Basis expansion, non-linear regression, degree, overfitting. Explanation: Polynomial regression extends linear regression by adding polynomial terms of the input features, allowing the model to capture curvature. Example: Modeling the relationship between welding current and bead penetration depth with a quadratic term to reflect diminishing returns at high currents. Practical application: Provides a simple yet expressive model for process planners adjusting welding parameters. Challenges: High-degree polynomials can lead to Runge's phenomenon (oscillatory behavior) and overfitting; regularization or cross-validation is essential.

Precision

Related terms: Positive predictive value, false discovery rate, classification threshold. Explanation: Precision quantifies the proportion of true positive predictions among all positive predictions: $TP / (TP + FP)$. In weld defect detection, high precision means most flagged defects are genuine. Example: A model that reports 100 defects, of which 90 are actual defects, achieves a precision of 0.90. Practical application: Reduces unnecessary re-work or inspection when false alarms are costly. Challenges: Precision alone does not reflect missed defects; optimizing precision may inadvertently lower recall, requiring a balanced approach.

Random Forest

Related terms: Bagging, bootstrap aggregation, feature randomness, out-of-bag error. Explanation: Random forest builds an ensemble of decision trees on bootstrapped subsets of data, each split considering a random subset of features. The final prediction aggregates (majority vote or average) across trees, reducing variance. Example: A random forest with 200 trees predicts weld spatter occurrence using current, voltage, and gas composition as inputs. Practical application: Robust to noisy sensor data and provides feature importance scores useful for welding process optimization. Challenges: Large ensembles increase memory usage; interpretability is lower than a single decision tree, though partial dependence plots can aid understanding.

Recall (Sensitivity)

Related terms: True positive rate, missed detection, false negative, class imbalance. Explanation: Recall measures the proportion of actual positives correctly identified: $TP / (TP + FN)$. In welding, high recall ensures most defects are caught. Example: Detecting 80 out of 100 actual cracks yields a recall of 0.80. Practical application: Critical when the cost of undetected defects (e.G., Structural failure) outweighs the cost of false alarms. Challenges: Maximizing recall alone may increase false positives, reducing precision; threshold tuning is required to balance both.

Regularization

Related terms: L1, L2, penalty term, overfitting control. Explanation: Regularization adds a penalty to the loss function to discourage complex models, helping prevent overfitting. L1 regularization (Lasso) promotes sparsity, while L2 (Ridge) shrinks coefficients uniformly. Example: Adding $\lambda \|\beta\|_2^2$ to a linear regression predicting weld bead geometry reduces sensitivity to measurement noise. Practical application: Enables stable models when welding datasets contain many correlated sensor channels. Challenges: Selecting the regularization strength λ requires validation; overly strong regularization can lead to underfitting.

Resampling Methods (Bootstrap, Jackknife)

Related terms: Statistical inference, confidence intervals, variance estimation. Explanation: Resampling techniques generate multiple pseudo-samples from the original data to assess estimator variability. Bootstrap draws samples with replacement; Jackknife systematically leaves out one observation at a time. Example: Bootstrapping the mean absolute error of a weld-quality predictor to construct a 95 % confidence interval. Practical application: Provides uncertainty estimates for model performance without assuming normality, valuable for safety-critical welding applications. Challenges: Computationally intensive for large datasets; bootstrap may underestimate variance when data are highly dependent.

ROC Curve (Receiver Operating Characteristic)

Related terms: AUC, true positive rate, false positive rate, threshold analysis. Explanation: The ROC curve plots TPR against FPR across varying classification thresholds, illustrating trade-offs between sensitivity and specificity. The area under the curve (AUC) summarizes overall discriminative ability. Example: A weld-defect classifier with $AUC = 0.93$ indicates strong separation between defective and sound welds. Practical application: Helps choose an operating point that balances safety (high recall) and productivity (low false alarm rate). Challenges: ROC can be misleading on imbalanced data; precision-recall curves may be more informative when defect prevalence is low.

Scaling (Normalization)

Related terms: Standardization, min-max scaling, feature scaling, data preprocessing. Explanation: Scaling transforms features to comparable ranges, preventing algorithms that rely on distance (e.G., K-NN, SVM) from being dominated by variables with larger numeric ranges. Common methods include Z-score standardization and min-max normalization. Example: Normalizing voltage (0–400V) and current (0–300A) to a 0-1 range before feeding them to a support vector machine. Practical application: Improves convergence speed for gradient-based optimizers in neural networks modeling welding processes. Challenges: Scaling parameters must be derived from training data only; applying them to test data incorrectly can cause data leakage.

Support Vector Machine (SVM)

Related terms: Kernel trick, margin maximization, hyperplane, soft margin. Explanation: SVM finds the hyperplane that maximally separates classes by maximizing the margin between support vectors. Kernels (linear, polynomial, radial basis function) enable nonlinear separation by mapping data into higher-dimensional spaces. Example: An RBF-kernel SVM distinguishes between stable and unstable arcs using time-frequency features extracted from voltage signals. Practical application: Provides strong performance on small-to-medium welding datasets with complex decision boundaries. Challenges: Choosing an appropriate kernel and tuning C (regularization) and γ (kernel width) is non-trivial; training scales poorly with large sample sizes.

Training Set

Related terms: Labeled data, supervised learning, data split, model fitting. Explanation: The training set consists of input-output pairs used to learn model parameters. In welding AI, it typically contains sensor measurements (inputs) and corresponding quality labels (outputs). Example: 1,500 Weld samples with recorded current, voltage, and manually inspected defect status form the training set for a classifier. Practical application: The foundation for any supervised algorithm; quality of labels directly impacts model reliability. Challenges: Obtaining accurately labeled welding data is costly; noisy or biased labels can propagate errors throughout the learning pipeline.

Underfitting

Related terms: High bias, low variance, model simplicity, poor training performance. Explanation: Underfitting occurs when a model is too simple to capture underlying patterns, resulting in high error on both training and validation data. Example: Using a linear regression to model the highly nonlinear relationship between welding speed and bead penetration leads to systematic prediction errors. Practical application: Signals the need for more expressive models (e.G., Decision trees, neural networks) or richer feature sets in welding process prediction. Challenges: Adding complexity without sufficient data can quickly shift the problem to overfitting; regularization helps balance model capacity.

Validation Set

Related terms: Hold-out, model selection, hyperparameter tuning, data leakage. Explanation: A validation set is a subset of data set aside from training to evaluate model performance during development, guiding hyperparameter choices. Example: Reserving 20% of weld samples as a validation set while training a random forest to predict porosity. Practical application: Provides an unbiased estimate of generalization

error before final testing. Challenges: With limited welding data, allocating a separate validation set reduces training data; cross-validation may be preferred.

Variable Importance (Feature Importance)

Related terms: Permutation importance, Gini importance, SHAP values, interpretability. Explanation: Variable importance quantifies the contribution of each feature to the predictive power of a model. Techniques differ by algorithm; for tree-based models, impurity reduction is common, while model-agnostic methods use perturbation. Example: In a gradient-boosted model, current, voltage, and gas flow rank as the top three important features for predicting lack-of-fusion defects. Practical application: Guides welding engineers to focus on controllable parameters that most affect quality, enabling targeted process improvements. Challenges: Importance scores can be biased toward high-cardinality or correlated features; careful interpretation and complementary visualizations are needed.

XGBoost (Extreme Gradient Boosting)

Related terms: Gradient boosting, regularized trees, learning rate, tree depth. Explanation: XGBoost is an optimized implementation of gradient boosting that adds regularization terms to control model complexity and uses second-order Taylor approximation for loss, enabling fast and accurate learning. Example: An XGBoost model with 500 trees predicts weld bead geometry from a combination of electrical and thermal sensor inputs. Practical application: Frequently achieves state-of-the-art performance on welding defect datasets while providing built-in handling of missing values. Challenges: Requires careful tuning of parameters such as `max_depth`, `eta` (learning rate), and `lambda` (L2 regularization) to avoid overfitting, especially on small welding datasets.

Zero-One Loss

Related terms: Misclassification error, classification loss, indicator function. Explanation: Zero-one loss assigns a loss of 0 for a correct prediction and 1 for an incorrect one. It directly measures classification error but is non-differentiable, making it unsuitable for gradient-based optimization. Example: In weld defect classification, a model that misclassifies 30 out of 1,000 samples incurs a zero-one loss of 0.03. Practical application: Used as a metric for evaluating final model performance after training with surrogate loss functions (e.g., Cross-entropy). Challenges: Optimization algorithms cannot minimize zero-one loss directly; surrogate losses may lead to models that are not truly optimal under zero-one loss.